


SECURITY PLANTATION SHUTTERS FROM SECURITY365

Our Security Plantation Shutters offer the strength of reinforced aircraft-grade aluminium combined with the timeless style of classic plantation shutters. Lockable and hinge-able, they eliminate the need for security bars/grilles, blinds or curtains. These powder-coated shutters are easily cleaned and never require repainting or re-varnishing. They provide protection from the sun's harmful rays yet still allow fresh air to circulate.

Versatile Security: Available in both a sliding and bi-fold system, your Security Plantation Shutters can be used as hinged security doors, sliding security doors, fixed window security shutters, sliding window security shutters, a patio enclosure and privacy screen, or a bi-folding door and window. They are suitable for commercial and residential applications, internal or external, and can be made to suit any rectangular opening.



Durable: Your environmentally friendly Security Plantation Shutters will not shrink, crack, fade or warp. Because you control the angle of the shutters, you can create a lovely, bright ambience while cutting down on the amount of UV light entering your building. This will preserve the life of carpets and furniture. Made from metal (aluminium), they offer obvious fire advantages and significant maintenance advantages over timber shutters and the like. They are highly water resistant enabling you to spend much more quality time relaxing outdoors. The durable finish is every bit as effective for both indoor and outdoor use.

Design: Security365's Security Plantation Shutter consists of an 88mm extruded aluminium aerofoil blade containing a reinforced core, which pivots on an 8mm machined solid axle, captured on both sides by a seamless aluminium security frame. Blades are connected to an operating rod located cleverly to the sides of the blades via acetyl bush that provides smooth and rattle free operation.

The controls conveniently located to the side of each shutter allow for a clear, uninterrupted view, and are easily wiped over when cleaning.

Patented Locking Systems: The plantation shutters swing on security hinges or slide in a security track and are locked with an integrated key operated lock, that when activated, throw a strong, stainless steel 8mm diameter locking pin into the surrounding frame or structure.

Hinged shutter doors are provided with triple locking. This is a mortise lock which has a handle and key cylinder assembly on the front and back of the door, and three locking tongues located in the centre (at the handle) plus both top and bottom rails, where they lock into the floor and doorway head.



Sliding doors are locked in place through the use of the security guide tracks at the top and bottom of the panel, and an Australian Standards Certified single or three-point key lock.

Flyscreening: French doors, casement and awning windows have always been difficult to provide screening, security and curtaining in the same opening. The solution is to combine attractive lockable aluminium shutters with detachable flyscreening. They close completely blocking out most of the light and are secure. Generally they are provided with easily operated turn-buttons, to allow for easy removal when they require cleaning.

Colours: Your plantation shutters will be supplied standard with a very durable and easily cleaned powder-coated finish. Our standard colours are "Interpon's - Satin White" or "Jotun's - Satin White Birch". Other powder coat colours are available on request with the satin finish recommended and at a moderate additional cost.

Australian Standards: Our hinged plantation shutters have undergone recent testing by a NATA approved laboratory to meet Australia Security Screen Standards AS5039 & AS5040.

Warranty: Our shutters are custom manufactured to ensure a perfect fit and come with a 5-year warranty on the louvre slats, frames and installation. Quality locks and other moving mechanisms are covered for a period of 12 months.

Get a no-obligation quote on your plantation shutters

We'll come to your premises to measure and quote, with no obligation on you. While we're there, we'll be able to answer any other security-related question you might have. Call us on 1300 365 557 today.

BLADE
BLADE TYPE
FRAME SIZES

88mm x 15mm GSELB
Elliptical Louvre Blade
Stiles 68mm x 29mm
GSDF

HINGES
CORNER STAKES

Top & Bottom Rail
68mm x 29mm GSDF
Mid Rail 50mm x 29mm
GSMR

Blade Control Bar GSCB
100mm Stainless Steel
Reinforced extruded
aluminium corner stakes

MATERIAL
MAXIMUM WIDTH

TS Extruded aluminium
Hinged 1000mm

Bi-fold 900mm

MAXIMUM HEIGHT
FINISH
STANDARD COLOURS

Sliders 1200mm
All Types 2600mm
Powder coated
Dulux Satin White

OTHER COLOURS

Dulux Satin White Birch
Dulux Classic Cream,
Dulux Precious Silver
Pearl, Jotun, Sahara
Black, Anotec XT Silver
Paperback, Azurite
Copper Pearl

WEIGHT
WARRANTY

Approx 13kg/m²
5 years on the louvre
slats and frames. Refer
to full warranty for
details